



265 East 100 South Suite 350


Salt Lake City, Utah 84111-1604 Ph (801) 521-8564 Fax (801) 355-INFORMATION


KEYED NOTES


CAMP W.G. WILLIAMS,
















175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com

GENERAL MECHANICAL


- DO NOT ROUTE DUCTS AND PIPES ABOVE ELECTRICAL PANELS. ALL ELECTRICAL PANELS MUST HAVE CLEAR ACCESS SPACE IN FRONT OF PANEL 4'-0" DEEP AND 6'-6" HIGH. DO NOT ROUTE DUCTS AND PIPES IN ELECTRICAL ROOMS, EXCEPT DUCTS AND PIPES SERVING THE ROOM.
- COORDINATE EXACT LOCATIONS OF CEILING DIFFUSERS AND GRILLES WITH ARCHITECTURAL REFLECTED CEILING PLAN.
- ALL DUCT DIMENSIONS ARE INSIDE FREE AREA DIMENSIONS. ADJUST SHEET METAL DIMENSION FOR LINED DUCT.
- 4. IF CONTRACTOR ENCOUNTERS MATERIAL WHICH MAY CONTAIN ASBESTOS IMMEDIATELY STOP WORK IN THIS AREA AND NOTIFY THE OWNER.
- PROVIDE CEILING ACCESS PANELS AS REQUIRED WHERE MECHANICAL EQUIPMENT, VALVES, VAV BOXES, FIRE DAMPERS, ETC. ARE LOCATED ABOVE INACCESSIBLE CEILINGS.
- 6. STEEL ROOF DECK SHALL NOT BE USED TO SUPPORT LOADS FROM PIPING, DUCTWORK OR EQUIPMENT, UNLESS NOTED OTHERWISE. HANGER LOADS LESS THAN 50 LBS. MAY BE HUNG FROM THE STEEL ROOF DECK IN CASES WHEN HANGING FROM THE STEEL ROOF DECK CANNOT BE AVOIDED: THE ATTACHMENT METHOD MUST DISTRIBUTE THE LOAD ACROSS THE DECK AS APPROVED BY THE STRUCTURAL ENGINEER.
- PROVIDE AND INSTALL CARRIERS AS REQUIRED FOR FLOOR AND WALL MOUNTED PLUMBING FIXTURES. INSTALL ALL FIXTURES WITH ACCESSORIES AS REQUIRED TO PROVIDE A COMPLETE, WORKABLE INSTALLATION.
- 8. PLUMBING FIXTURES SHALL INCLUDE COMPRESSION STOPS ABOVE FLOOR IN SUPPLIES TO ALL FIXTURES AND A MINIMUM 17 GAUGE P-TRAP
- ALL LAVATORIES AND HAND SINKS WILL HAVE A COMBINATION FAUCET OR PREMIXING FAUCET CAPABLE OF SUPPLYING WARM WATER FOR A MINIMUM OF 10 SECONDS.
- 10. FLOOR DRAINS ARE SHOWN IN THE APPROXIMATE LOCATION. COORDINATE FINAL LOCATION WITH EQUIPMENT AND DRAINAGE REQUIREMENTS. PROVIDE BLOCKOUTS AS NECESSARY.
- 11. PROVIDE ALL LABOR, MATERIALS, AND EQUIPMENT NECESSARY TO CONSTRUCT A COMPLETE, OPERATIONAL PLUMBING SYSTEM FOR THE ENTIRE PROJECT AS SHOWN ON THESE DRAWINGS, INCLUDING ALL NECESSARY FEES AND PERMITS.
- 12. THE ENTIRE INSTALLATION SHALL CONFORM TO THE REQUIREMENTS OF THE MOST RECENTLY ADOPTED BUILDING CODE, MECHANICAL CODE, PLUMBING CODE, ELECTRICAL CODE, AND ALL OTHER APPLICABLE CITY, COUNTY, SCHOOL DISTRICT, STATE, AND FEDERAL CODES AND REGULATIONS IN EFFECT AT THE DATE OF THE BID. CONFORM TO ANY CODES, RULES, REGULATIONS AND REQUIREMENTS THAT THE PROJECT OWNER HAS.
- 13. THE DRAWINGS AND SPECIFICATIONS HAVE BEEN PREPARED TO SUPPLEMENT EACH OTHER AND THEY SHALL BE INTERPRETED AS AN INTEGRAL UNIT WITH THE ITEMS SHOWN ON ONE AND NOT THE OTHER BEING FURNISHED AND INSTALLED AS THOUGH SHOWN AND CALLED OUT IN BOTH.



Utah National Guard

New Guard House CAMP W.G.WILLIAMS, UTAH

SHEET TITLE							
Me	chanic	26	I Co	ver	Sh	eet	
REVISIONS	DATE		ВУ	DESCR	IPTION		
DRAWN BY	PS:	S	CHECKED BY				DLA
PROJECT NO.	06286480)	DRAWING NO.		4	_	








175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com

○SHEET KEYNOTES

- RUN PIPING TIGHT TO INTERIOR SIDE OF 2X6 FRAMED WALL. PROVIDE BATT INSULATION BETWEEN PIPES AND EXTERIOR WALL. IN ADDITION TO PIPE INSULATION. TYPICAL.
- 2. SEE SITE PLAN FOR CONTINUATION.
- 3. PRESSURE FLUCTUATION TYPE TRAP PRIMER.
- DROP PIPES TO SINK IN WALL, TURN UNDER WINDOW, AND ENTER CABINET UNDER SINK.



SHEET TITLE	chanci	al F		ans
REVISIONS	DATE	ВУ		DESCRIPTION
\triangle				
\triangle				
\triangle				
DRAWN BY	PSS	CHECKED) BY	DLA
	06286480	DRAWIN	IG NO.	.
DATE 2 (006-09-07			M-103









175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com







ABBREVIATIONS

NOTE: ALL ABBREVIATIONS MAY NOT BE USED.

5

	NOTE: ALL ABBREVIATI	ONS MAY	NOT BE USED.
1P 1PH	SINGLE POLE SINGLE-PHASE	KV KVA	KILOVOLT KILOVOLT AMPERE
1WAY	ONE-WAY	kVAR	KILOVOLT AMPERE
2/C	TWO-CONDUCTOR		REACTIVE
2WAY 3/C	TWO-WAY THREE-CONDUCTOR	kW kWh	KILOWATT KILOWATT HOUR
3PH	THREE-PHASE	LED	LIGHT EMITTING DIODE
3WAY 4OUT	THREE-WAY QUADRUPLE RECEPTACLE	LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
4001	OUTLET	LFNC	LIQUID TIGHT FLEXIBLE
4PDT	FOUR-POLE DOUBLE	LPS	NONMETALLIC CONDUIT LOW PRESSURE SODIUM
4PST	THROW FOUR-POLE SINGLE	LRA	LOCKED ROTOR AMPS
4114	THROW	LTG	LIGHTING
4W 4WAY	FOUR-WIRE FOUR-WAY	LV MATV	LOW VOLTAGE MASTER ANTENNA
Α	ABOVE COUNTER		TELEVISION SYSTEM
AC ADA	ARMORED CABLE AMERICANS WITH	MAX MC	MAXIMUM METAL CLAD
	DISABILITIES ACT	МСА	MINIMUM CIRCUIT AMPS
ADJ AFF	ADJACENT ABOVE FINISHED FLOOR	MCB MCC	MAIN CIRCUIT BREAKER MOTOR CONTROL CENTER
AFG	ABOVE FINISHED GRADE	MCP	MOTOR CIRCUIT
AIC	AMPERE INTERRUPTING CAPACITY	MDP	PROTECTION MAIN DISTRIBUTION
ALUM	ALUMINUM		PANEL
AMP ANN	AMPERE ANNUNCIATOR	MG MH	MOTOR GENERATOR MANHOLE
AP	ACCESS POINT	MIN	MINIMUM
AR	(WIRELESS DATA) AS REQUIRED	MLO MOCP	MAIN LUGS ONLY MAXIMUM OVERCURRENT
ASC	AMPS SHORT CIRCUIT		PROTECTION
ATS	AUTOMATIC TRANSFER	NA NC	NOT APPLICABLE NORMALLY CLOSED
AV	SWITCH AUDIO VISUAL	NEC	NATIONAL ELECTRICAL
AWG	AMERICAN WIRE GAGE	NEMA	CODE NATIONAL ELECTRICAL
	BUCK-BOOST TRANSFORMER	INCINA	MANUFACTURERS
С	CEILING MOUNTED	NFC	ASSOCIATION NATIONAL FIRE CODE
CATV	COMMUNITY ANTENNA TELEVISION	NFPA	NATIONAL FIRE
CB	CIRCUIT BREAKER	NIC	PROTECTION ASSOCIATION NOT IN CONTRACT
CCBA	CUSTOM COLOR AS SELECTED BY ARCHITECT	NL NL	NIGHT LIGHT
CCTV	CLOSED CIRCUIT	NO	NORMALLY OPEN
CFBA	TELEVISION CUSTOM FINISH AS	NTS OC	NOT TO SCALE ON CENTER
	SELECTED BY ARCHITECT	OCP	OVER CURRENT
CF/CI	CONTRACTOR FURNISHED/ CONTRACTOR INSTALLED	OF/CI	PROTECTION OWNER FURNISHED/
CF/OI	CONTRACTOR FURNISHED/		CONTRACTOR INSTALLED
CKT	OWNER INSTALLED CIRCUIT	OF/OI	OWNER FURNISHED/ OWNER INSTALLED
CM	CONSTRUCTION MANAGER	OFP	OBTAIN FROM PLANS
CND CO	CONDUIT CONVENIENCE OUTLET	OH DR	OVERHEAD (COILING) DOOR
COR	CONTRACTING OFFICER'S	OL PB	OVERLOAD
CP	REPRESENTATIVE CONTROL PANEL	PF	PUSHBUTTON POWER FACTOR
CT	CURRENT TRANSFORMER	PH PNL	PHASE PANEL
CTV CU	CABLE TELEVISION COPPER	PT	POTENTIAL TRANSFORMER
dBA	UNIT OF SOUND LEVEL	PTZ QTY	PAN/TILT/ZOOM QUANTITY
DPDT	DOUBLE POLE DOUBLE THROW	R	REMOVE
DS	DISCONNECT SWITCH	RCP RMC	REFLECTED CEILING PLAN RIGID METAL CONDUIT
EA EC	EACH EMPTY CONDUIT	RNC	RIGID NONMETALLIC
EM	EMERGENCY FLECTRICAL METALLIC	RPM	CONDUIT REVOLUTIONS PER MINUT
EMT	ELECTRICAL METALLIC TUBING	RR	REMOVE AND RELOCATE
ENT	ELECTRICAL NONMETALLIC	SCA SCBA	SHORT CIRCUIT AMPS
EPO	TUBING EMERGENCY POWER OFF		STANDARD COLOR AS SELECTED BY ARCHITECT
EQUIP EXIST	EQUIPMENT	SF SFBA	SQUARE FOOT (FEET) STANDARD FINISH AS
F	EXISTING FURNITURE MOUNTED		SELECTED BY ARCHITECT
FA	FIRE ALARM	SPDT	SINGLE POLE, DOUBLE THROW
FCP	FIRE ALARM CONTROL PANEL	SPEC	SPECIFICATION
FLA	FULL LOAD AMPS	SPST	SINGLE POLE, SINGLE THROW
FMC FOB	FLEXIBLE METALCONDUIT FREIGHT ON BOARD	s/s	START/STOP
FVNR	FULL VOLTAGE	ST SWBD	SINGLÉ THROW SWITCHBOARD
FVR	NON-REVERSING FULL VOLTAGE REVERSING	SWGR	SWITCHGEAR
G	GROUND	TL TP	TWIST LOCK
GEN GFCI	GENERATOR GROUND FAULT CIRCUIT	TP	TELEPHONE POLE TWISTED PAIR
	INTERRUPTER	TTB	TELEPHONE TERMINAL
GFP	GROUND FAULT PROTECTION	TV	BOARD TELEVISION
HD	HEAVY DUTY	TVSS	TRANSIENT VOLTAGE
HID	HIGH INTENSITY DISCHARGE	TYP	SURGE SUPPRESSER TYPICAL
НОА	HAND-OFF-AUTOMATIC	UF	UNDERFLOOR
HP HPF	HORSE POWER HIGH POWER FACTOR	UGND UPS	UNDERGROUND UNINTERRUPTIBLE POWER
HPS	HIGH PRESSURE SODIUM		SUPPLY
HV HZ	HIGH VOLTAGE HERTZ	V VA	VOLTS VOLT AMPERE
IG	ISOLATED GROUND	VFC	VARIABLE FREQUENCY
IMC	INTERMEDIATE METAL CONDUIT	w/	CONTROLLER WITH
IN/IS	INSULATED/ISOLATED	W/O	WITHOUT
I/O IR	INPUT/OUTPUT INFRARED	WP XFMR	WEATHERPROOF TRANSFORMER
J-BOX	JUNCTION BOX		
		_	

GENERAL ELECTRICAL NOTES

- 1. CLARIFICATION METHODS: AT THE TIME OF BIDDING, BIDDERS SHALL FAMILIARIZE THEMSELVES WITH THE DRAWINGS AND SPECIFICATIONS. ANY QUESTIONS, MISUNDERSTANDINGS, CONFLICTS, DELETIONS, DISCONTINUED PRODUCTS, CATALOG NUMBER DISCREPANCIES, DISCREPANCIES BETWEEN THE EQUIPMENT SUPPLIED AND THE INTENT OR FUNCTION OF THE EQUIPMENT, ETC, SHALL BE SUBMITTED TO THE ARCHITECT/ENGINEER IN WRITING FOR CLARIFICATION PRIOR TO ISSUANCE OF THE FINAL ADDENDUM AND BIDDING OF THE PROJECT. WHERE DISCREPANCIES OR MULTIPLE INTERPRETATIONS OCCUR, THE MOST STRINGENT (WHICH IS GENERALLY RECOGNIZED AS THE MOST COSTLY) THAT MEETS THE INTENT OF THE DOCUMENTS SHALL BE ENFORCED.
- 2. OWNER FURNISHED ITEMS: THE OWNER WILL FURNISH MATERIAL AND EQUIPMENT AS INDICATED IN THE CONTRACT DOCUMENTS TO BE INCORPORATED INTO THE WORK. THESE ITEMS ARE ASSIGNED TO THE INSTALLER AND COSTS FOR RECEIVING, HANDLING, STORAGE, IF REQUIRED, AND INSTALLATION ARE INCLUDED IN THE CONTRACT SUM.
 - A. THE INSTALLER'S RESPONSIBILITIES ARE THE SAME AS IF THE INSTALLER FURNISHED THE MATERIALS OR EQUIPMENT.
 - B. THE OWNER WILL ARRANGE AND PAY FOR DELIVERY OF OWNER FURNISHED ITEMS FREIGHT ON BOARD JOB SITE AND THE INSTALLER WILL INSPECT DELIVERIES FOR DAMAGE. IF OWNER FURNISHED ITEMS ARE DAMAGED, DEFECTIVE OR MISSING, DOCUMENT DAMAGED ITEMS WITH THE TRANSPORT COMPANY AND THE OWNER WILL ARRANGE FOR REPLACEMENT. THE OWNER WILL ALSO ARRANGE FOR MANUFACTURER'S FIELD SERVICES, AND THE DELIVERY OF MANUFACTURER'S WARRANTIES AND BONDS TO THE INSTALLER.

C. THE INSTALLER IS RESPONSIBLE FOR DESIGNATING THE DELIVERY

DATES OF OWNER FURNISHED ITEMS AND FOR RECEIVING, UNLOADING AND HANDLING OWNER FURNISHED ITEMS AT THE SITE. THE INSTALLER IS RESPONSIBLE FOR PROTECTING OWNER FURNISHED ITEMS FROM DAMAGE, INCLUDING DAMAGE FROM EXPOSURE TO THE ELEMENTS, AND TO REPAIR OR REPLACE ITEMS DAMAGED AS A RESULT OF HIS OPERATIONS.

3. EXPOSED STRUCTURE AREAS (EXCLUDING MECHANICAL, ELECTRICAL, AND

COMMUNICATION SPACES): INSTALL RACEWAYS BETWEEN DECK AND STRUCTURE WHEREVER POSSIBLE IN EXPOSED STRUCTURE CEILING AREAS.

ROUTE RACEWAYS IN CONCEALED AREAS WHEREVER POSSIBLE. REFER ALL CONDITIONS WHERE RACEWAYS MUST BE INSTALLED WHICH CANNOT COMPLY WITH THESE REQUIREMENTS TO THE ARCHITECT.

4. SUBMITTALS: PROVIDE SUBMITTALS IN THREE RING BINDERS WITH JOB NAME, SUBCONTRACTOR, AND VOLUME ON THE BINDING. PREPARE TABS

FOR EACH SPECIFICATION SECTION REQUIRING SUBMITTALS. PREPARE INDEX

5. REFLECTED CEILING PLANS: COORDINATE THE LOCATION OF LIGHT FIXTURES WITH THE ARCHITECTURAL REFLECTED CEILING PLANS. REFER ALL DISCREPANCIES TO THE ARCHITECT AND ENGINEER.

OF EQUIPMENT SUBMITTED IN EACH TAB.

DEFINITIONS

NOTE: ALL DEFINITIONS MAY NOT BE USED.

INDICATED: THE TERM "INDICATED" REFERS TO GRAPHIC REPRESENTATIONS, NOTES, OR SCHEDULES ON THE DRAWINGS, OTHER PARAGRAPHS OR SCHEDULES IN THE SPECIFICATIONS, AND SIMILAR REQUIREMENTS IN THE CONTRACT DOCUMENTS. WHERE TERMS SUCH AS "SHOWN", "NOTED", "SCHEDULED", AND "SPECIFIED" ARE USED, IT IS TO HELP THE READER LOCATE THE REFERENCE, NO LIMITATION ON LOCATION IS INTENDED.

DIRECTED: TERMS SUCH AS "DIRECTED", "REQUESTED", AUTHORIZED", "SELECTED", "APPROVED", "REQUIRED", AND "PERMITTED" MEAN "DIRECTED BY THE ENGINEER", "REQUESTED BY THE ENGINEER", AND SIMILAR PHRASES.

APPROVED: THE TERM "APPROVED", WHERE USED IN CONJUNCTION WITH THE ENGINEER'S ACTION ON THE CONTRACTOR'S SUBMITTALS, APPLICATIONS, AND REQUESTS, IS LIMITED TO THE ENGINEER'S DUTIES AND RESPONSIBILITIES AS STATED IN GENERAL AND SUPPLEMENTARY CONDITIONS.

FURNISH: THE TERM "FURNISH" IS USED TO MEAN "SUPPLY AND DELIVER TO THE PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS."

INSTALL: THE TERM "INSTALL" IS USED TO DESCRIBE OPERATIONS AT PROJECT SITE INCLUDING THE ACTUAL "UNLOADING, UNPACKING, ASSEMBLY, ERECTION, PLACING, ANCHORING, APPLYING, WORKING TO DIMENSION, FINISHING, CURING, PROTECTING, CLEANING, AND SIMILAR OPERATIONS."

PROVIDE: THE TERM "PROVIDE" MEANS "TO FURNISH AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE."

INSTALLER: AN "INSTALLER" IS THE CONTRACTOR OR AN ENTITY ENGAGED BY THE CONTRACTOR, EITHER AS AN EMPLOYEE, SUBCONTRACTOR, OR SUB-SUBCONTRACTOR, FOR PERFORMANCE OF A PARTICULAR CONSTRUCTION ACTIVITY, INCLUDING INSTALLATION, ERECTION, APPLICATION, AND SIMILAR OPERATIONS. INSTALLERS ARE REQUIRED TO BE EXPERIENCED IN THE OPERATIONS THEY ARE ENGAGED TO PERFORM.

TECHNOLOGY SYSTEMS: THE TERM "TECHNOLOGY SYSTEMS" IS USED TO DESCRIBE ALL LOW VOLTAGE SYSTEMS GENERALLY REFERRED TO AS "SPECIAL SYSTEMS". THESE SYSTEMS INCLUDE BUT ARE NOT NECESSARILY LIMITED TO ALL SYSTEMS WHICH UTILIZE VOLTAGES OF LESS THAN 71 VOLTS SUCH AS SOUND SYSTEMS, VIDEO SYSTEMS, TV SYSTEMS, SECURITY SYSTEMS, VOICE AND DATA CABLING SYSTEMS,

ELECTRICAL SHEET INDEX SHEET NO SHEET TITLE E-001 SYMBOL LEGEND/SHEET INDEX E-101 ELECTRICAL SITE PLN E-102 **DEMOLITION PLANS** E-103 ELECTRICAL PLANS E-501 DETAILS DETAILS E-502 E-601 SCHEDULES



ris & Associates


265 East 100 South Suite 350 Salt Lake City, Utah 84111-1604 Ph (801) 521-8564 Fax (801) 355-2938



175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com



SHEET TITLE					
Syn	nbol L	_6	geno	d/Sheet	Index
REVISIONS	DATE		ВУ	DESCRIPTION	
\triangle					
\triangle					
\triangle					
DRAWN BY	PS	S	CHECKED BY		DLA
PROJECT NO.	0628648	0	DRAWING NO.		204
DATE 2	006-09-0	7		L-(001








175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com


○SHEET KEYNOTES

- 1. UNDER BASE BID: PROVIDE 4—INCH CONDUIT WITHOUT INNERDUCT FOR COMMUNICATION STUBBED AND CAPPED TO 5—FEET OUTSIDE THE BUILDING.
- ADD ALT #1: PROVIDE ADD ALTERNATE PRICING FOR COMMUNICATIONS CONDUIT TO EXTEND TO COMMUNICATION MANHOLE APPROXIMATELY 420—FEET AWAY.
- EXISTING UNDERGROUND COMMUNICATIONS LINE AND MANHOLE. NEW 4—INCH COMMUNICATIONS CONDUIT TO TIE INTO EXISTING MANHOLE UNDER ADD. ALTERNATE #1.



SHEET TITLE	ctrical		Site	Plan
REVISIONS			ВУ	DESCRIPTION
\triangle				
\triangle				
\triangle				
DRAWN BY	PS	S	CHECKED BY	DLA
PROJECT NO.	0628648	0	DRAWING NO.	F 404
DATE 2	006-09-0	7		E-101









175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com


○SHEET KEYNOTES

- PROVIDE WIREMOLD 4000 OR EQUAL. DUAL CHANNEL STEEL RACEWAY. MOUNT 6-INCHES ABOVE THE COUNTERTOP.
 - MOUNT SURFACE WIREMOLD IN MILLWORK. COORDINATE WITH MILLWORK INSTALLER.
- 3. PROVIDE UFER GROUND IN NEW CONCRETE FOUNDATION AT APPROXIMATELY THIS LOCATION. BOND TO REBAR.
- 4. CONNECT EXHAUST FAN TO LIGHTING CIRCUIT AND CONTROL WITH LIGHTS.
- 5. PROVIDE 0.75-INCH CONDUIT WITH PULL STRING.
- 6. MOUNT JUNCTION BOX IN WALL AT LIGHT SWITCH HEIGHT.
- MOUNT 4-SQUARE JUNCTION BOX IN SOFFIT. PROVIDE GASKETED COVER PLATE.
- 8. RECONNECT RELOCATED SECURITY/FIRE PANEL TO MATCH PREVIOUS SETUP AND OPERATION. REPROGRAM AND TEST AS REQUIRED. VERIFY REQUIREMENTS WITH UTAH NATIONAL GUARD PRIOR TO BIDDING.
- RECONNECT EXISTING SPRINKLER CONTROLS TO NEW PANEL. FIELD VERIFY LOCATION AND REQUIREMENTS.
- 10. PROVIDE OUTLET AND CATV RACEWAY AT +84" AFF FOR POWER TO TV AND VCR. COORDINATE LOCATION OF DEVICES WITH UTAH NATIONAL GUARD PRIOR TO ROUGH IN.



Utah National Guard

Electrical Plans DESCRIPTION 06286480



Salt Lake City, Utah 84111-1604 Ph (801) 521-8564 Fax (801) 355-2938


175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com

GENERAL SHEET NOTES

- PROVIDE NEMA 3R ENCLOSURES FOR EQUIPMENT LOCATED OUTDOORS. REFER TO PLANS FOR EQUIPMENT LOCATIONS.
- REFER TO PLANS FOR CONSTRAINTS ON PHYSICAL DIMENSIONS AND CLEARANCE REQUIREMENTS OF EQUIPMENT. PROVIDE EQUIPMENT DIMENSIONS THAT FALL WITHIN THE CONSTRAINTS OF EACH SPECIFIC LOCATION.
- ALL EQUIPMENT SHALL BE CONSTRUCTED AND BRACED FOR THE SEISMIC CONDITIONS OF THE PROJECT. REFER TO SPECIFICATIONS SECTION 16071 FOR REQUIREMENTS.



1						
	SHEET TITLE Det	_				
	REVISIONS	DATE		ВУ	DESCRIPTION	
	\triangle					
	\triangle					
	\triangle					
	\triangle					
	DRAWN BY	PS	S	CHECKED BY		DLA
	PROJECT NO.	0628648	0	DRAWING NO.	Гго	
	DATE 2 0	006-09-0	7		E-50) [





175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com

Utah National Guard New Guard House CAMP W.G.WILLIAMS, UTAH

DESCRIPTION

06286480 E-502

18	17	16	15	14	13	12	11	1	10	9		3	7	6	5		4		3	2	1	
					PANEL	"1LA) 5							LIGHTIN	NG FIX	(TURE	SCHE	DULE	- -			
		VOLTS/PHASE/W 120/208 V, 3 PI	H 4 WIRE 2	ANEL SIZE & TYPE: 2" W × 6" D, BOLT—ON IDENTIFICATION, GROUND	MAIN SIZE & 100 AMPERE	MAIN BKR	OCATION:	CABINET: SURFACE				NOTE TO BIDDERS: REFER TO SPECIFIC	ATIONS FOR IMPOR	TANT TECHNICAL	REQUIREMENTS	FOR LIGHTIN	G FIXTURES, BAL					A
		CKT OCP NO AMP POLE	LOAD (kVA) LTG CO PWR	DESCRIPTION	LCL PHASE	LOAD LCL B C kVA	DESCRIPTION		D PWR AMP Po	CKT POLE NO		BELOW HAVE BEEN EACH MANUFACTUR NOTIFY THE ARCHIT	RER SHALL COMPAR	E THE CATALOG ANY DISCREPANO	NUMBERS SHO CIES. SPECIFICA	WN WITH THE LLY INCLUDED	DESCRIPTION AND IN THIS EVALUA	ID REQUIREM ATION SHALL	MENTS ON THE DA BE THE VERIFY	RAWINGS, AND S	HALL MOUNTING	
		1 20 1 3 20 1 5 30 1	0.4	TELEPHONE BOARD TELEPHONE BOARD ELECTRIC WATER HEATE	0.4 1.2 0.4 1. R 2.5	1.0 4 1.3 2.5 0.0	LIGHTING/EF-1 FLOOD LIGHTING SPARE		0.1 20 20 20	1 2 1 4 1 6		KITS OR ACCESSOR FOR DISCREPANCIES REPORTING OF ANY	S THAT WERE NOT	REPORTED TO TH	HE ARCHITECT/	ENGINEER IN	TIME FOR CORRE	CTION OR C	LARIFICATION BEF	FORE THE BID.	HE	
		7 20 1 9 20 1	0.2	RESTROOM REFRIGERATOR	0.2 1.6 1.0 2.	1.4 4 1.4	TWU-1 		1.4 30 1.4 –	2 8 - 10		FOR EACH FIXTURE PRODUCTS AND EM	TYPES SHOWN WIT	THIN 48 BUSINESS EER TO DETERMIN	S HOURS OF THE FAIR VALUE	HE BID DATE. FOR FIXTURE	FAILURE TO COM	MPLY WITH TON CHANGES	THIS REQUIREMEN S, WITHOUT FURT	T MAY DISQUAL HER INPUT FRO	FY THE M THE	
3		11 20 1 13 20 1 15 20 1	0.2 1.0 0.4	COUNTER COFFEE BREAK	0.2 1.0 1.6 0.4 0.	0.7 0.5 0.8 9 0.5	SEC/FIRE PANEL EXTERIOR LIGHTS SPRINKLER CONTROL	0.6	0.5 20 20 0.5 20	1 14		CONTRACTOR OR IN PENDANT MOUNTED AND INSTALLED AT	FIXTURES, PROVID	E A SECOND SET	T OF PENDANTS	G, OF A DIFFE	RENT LENGTH, A	S DIRECTED	BY THE ARCHITE	ECT/ENGINEER, I	PROVIDED	В
		17 20 1 19 20 1 21 20 1	0.6 0.6 0.6	EXTERIOR OUTLETS ISLAND WIREMOLD SECURITY DESK WM	0.6 0.6	1.1 0.5 0.0 6 0.0	TV/VCR SPARE SPARE		0.5 20 20 20	1 20		INTENDED AND WITH CONTRACTOR AND ALLOWANCE PRICE	ELECTRICAL DISTRIE	BUTOR SHALL VE	RIFY THIS ALLO	WANCE AND	REPORT ANY PRO	OBLEMS TO	THE ENGINEER BE	EFORE THE BID.	777)	
		23 20 1 25 20 1	0.6 0.6	SECURITY DESK WM SECURITY DESK WM	0.6 0.6 0.6	0.6 0.0	SPARE SPARE		20 20	1 24 1 26		BALLASTS REQUIREI F	D UNLESS NOTED (TIXTURE CHARACTER	OTHERWISE. RISTICS	J OK TREIGHT	AS NOTED, AI	ND DO NOT INCL	ODE ANT TA	TALS. UNIVERSAL			
		27 20 1 29 20 1 31 20 1	0.6 0.6 0.4	SECURITY DESK WM SECURITY DESK WM SECURITY DESK WM	0.6 0. 0.6 0.4 0.4	6 0.0 0.6 0.0 0.0	SPARE BLANK BLANK		20 20 20	1 30		SYMBOL MARK L	BODY / AIR / MOU .ENS/LOUVER/REFL FLUORESCENT DOWN	ECTOR/OTHER			MANUFACTUR			CTOR ASSEMBLIE	NOTES	C
		33 20 1 35 20 1	0.2	EXTERIOR OUTLET GENERAL RECEPTACLES	0.2 0. 0.8	2 0.0 0.8 0.0	BLANK BLANK		20 20	1 34 1 36		F 	FOR LAMPS AS LIST #); SELF FLANGING	TED BELOW; ELECTION TRIM UNLESS NO	CTRONIC BALLAS DTED.	STS; LOW IRID	ESCENT REFLECT	FOR FINISH (EVEN IF NOT SH	OWN IN CATALO	G	
		37 20 1 39 20 1 41 20 1		SPARE SPARE SPARE	0.0 0.0 0.0 0. 0.0	0.0 0 0.0 0.0 0.0	BLANK BLANK BLANK		20 20 20	1 38 1 40 1 42		T	RECESSED DOWNLIGH FRIM, FRESNEL LENS EA 26W QUAD LAMF	5, 2	2-Q26 80 RE835)W 277/1	20V INFINITY HALO PRESCOLITE	H803HP-	226Q—EB (G24Q —803P RDEB—90F71—MOD			
		TOTALS:		CONNECTED KVA PE CONNECTED AMPS PE	ER PHASE 6 6	6		CONNECTED AVERAGE AMPS	O TOTAL KVA	18			APERTURE, ROUND.	, • • •			LIGHTOLIER LITHONIA	8096FWV LGF 2/2	WH/7226HU 26DTT 9RW FFL N	IVOLT		
		LIGHTING	D LOAD CALCULATION 2kVA @125% = 7kVA @100% =	ONS 3 kVA 7 kVA	ALL OTHER LOA 25% OF LARGE		9 kVA O kVA	DIVERSIFIE AVERAGE AMPS	ED TOTAL KVA				RECESSED DOWNLIGH	•	2-Q26 80 RE835)W 277/1	OMEGA 20V HALO PRESCOLITE	H803HP-	H26QPL—U—T82H: —803P—EM RDEBEM—F71—MOD			D
			0kVA @ 50% =	0 kVA	20% OF LARGE	_O I IVIO I OR =	U KVA	AVENAGE AMPS	O I LIV FUASE	_ 33		E A	EA 26W QUAD LAMF APERTURE, ROUND.	PS, 8-10" (EMERGENCY)			LIGHTOLIER LITHONIA	8096FWH LGF 2/2	HW/7226HU EM 26DTT 9RW FFL N	NVOLT EL		
					CTAND AD	D 7411017.1	0 00///00 0	OHEDIN 5	_				PROVIDE 'IC' RATED PREFIX INDICATES		S PROVIDED WI	TH AN EMFRO	OMEGA INFINITY SENCY BATTERY I	PHRL75	H26QPL—IE—U—T8 226Q—EB_(G24Q ROVIDE_POWER_T0	-3) EM FF 277		
				NOTE TO BIDDER	RS: COMPLY WITH	SECTION 16140	OF THE SPECIFICATIONS	S. THE CATALOG	NUMBERS LIST			4	4 OR 8 FOOT FLOU TO PROVIDE 90 MIN	RESCENT LAMP (UTES OF EMERGE	COMPATIBLE WIT	TH ALL STAND O FIXTURE BA	ARD AND ELECTI LLAST; MINIMUM	RONIC BALLA LIGHT OUTP	ASTS; COMPLETEL PUT FOR TYPICAL	Y SELF-CONTA 4' LAMP SHALI		
				WITH THE OBJECT	IVE OF ASSISTING	THE BIDDERS II	E ASSISTANCE OF THE M N DETERMINING THE QUA ERS MAY NOT BE COMPL	ALITY AND RATIN	NGS OF THE WI	'IRING		T	BE 1100 LUMENS OF FEST SWITCH AND A NO DISASSEMBLY FO	AC "ON" INDICATO			-				s	E
				BELOW, BUT SHALL	BE SELECTED BY T	THE ARCHITECT	ED TO BE DETERMINED E AS INDICATED IN THE S	SPECIFICATION. I	EACH MANUFA	ACTURER			MERGENCY BATTER		12	0/277V3W	IOTA BODINE	I-80 B50				
				NEMA		HITECT/ENGINEE	ERS SHOWN WITH THE DER OF ANY DISCREPANCE	DIES.	G NUMBERS	Y IHE							LITHONIA PRESCOLITE EELP			ISTALLED)		
				NEMA 5-20R	20A, 12 RECEPTA	5V 2 POLE 3 V ACLES. NYLON	MIRE DUPLEX GROUNDING OR LEXAN FACES. BACK	G BRYANT K HUBBELL	5352 L CR5352								CHLORIDE LIGHTOLIER	CFP841 FBP50		,		
				NEMA 5-20R	AND UL	498.	PLY WITH FS W—C—596 MIRE DUPLEX FEED THRU	LEVITON P&S 535 U BRYANT					/ANDAL RESISTANT JV STABILIZED; ALL						· ·	· · · · · · · · · · · · · · · · · · ·		F
				GFCI	GFCI RE OR LEXA	CEPTACLES WIT AN DECORATOR	H INDICATOR LIGHT. NYL FACES. BACK AND SIDE	LON HUBBELL LEVITON	L GF5352 6898			V-2 4	MOUNTING; PROGRA 1', 2-LAMP WITH P	M START ELECTR RISMATIC	ONIC BALLASTS 2-F32T8 65	S; T8 LAMPS.	KENALL	N1048-0	C-232SB1-120/2	277-CM(682)		
_					WITH FS		PONENTS SHALL COMPLY ERE APPLICABLE. AND UL 493.	P&S 209	91 S			3	.ENS: 51" X 9 1/2 3 1/2"; WITH CORN MOUNTING ADAPTER	ER	RE835		CD LIGHTING LUMINAIRE NEW STAR	LVP-751	-S-232-UNV-EB 1-232-EBPS-120 /45-U-T8PROGR	D-COR		
				NEMA 5-20R WATERPROOF	20A, 12 RECEPTA	5V 2 POLE 3 V ACLES. NYLON	MIRE DUPLEX GROUNDING OR LEXAN FACES. BACK	<	L CR5352/5051	1-0		V S	NALL MOUNT; 16 G. STEEL.	AUGE			FAIL—SAFE HOLCOR	FPS-232 HSP2-2,	2-UNV-PROGRAM /32T8-120-ELB-	N START-2592 -CMA-UNIVOLT-	PROGRAM STA	RT
				(WEATHERPROOF IN USE)	AND UL		PLY WITH FS W—C—596 ASKETED WEATHERPROOF JRE.					A	LOW PROFILE WRAP, ACRYLIC PRISMATIC ELECTRONIC BALLAS	DIFFUSER; WHITE	E ENAMEL ENDF	PLATES; MINIM	IUM CU OF 70 @	80/50/20	AND RCR=1; PR			G
				20A SINGLE POLE	20A SIN SWITCH	GLE POLE 125\ LABELED AS C	V—277V STANDARD TOGO OMPLYING UL STANDARD	D LEVITON	1221			W-3 N	ON THE PLANS. NARROW BODY WRA	PAROUND;	2-F32T8 65		20V LITHONIA	LB232-N	MVOLT-TUBPHP			
					PROVIDE		SPECIFICATION W—S—89 XAN FACE, BACK AND S 20V.						2-LAMP, APPROX; < 48".	ى X 10″	RE835		DAYBRITE METALUX LIGHTOLIER	WS-232	-UNV-1/2-EB-S A-UNV-PROGRAN U-SOP			
				20A THREE-WAY	SWITCH	LABELED AS C	V-277V STANDARD TOGO OMPLYING UL STANDARD	D LEVITON	1223								LSI COLUMBIA	PR 232	SS010PRS UE 2-EBPS120/277			
					PROVIDE		SPECIFICATION W—S—89 XAN FACE, BACK AND S 20V.															H
				_	,			,														
														`^!! _		101/ /4	2011					
							MARK ITE	EM DESCRIPTION		LOAD DATA	·A I	EQUIP WIRE AND	MENT S	CHEDU	JLE 2(J&Y/1	20V OVERCURRENT	-		NOTES	MARK	
											VOLT PH Hz	CONDUIT SIZE (CC-INDICATE	s	CUNTO		DISCONNECT S	PROTECTION WITCH		CIRCUIT BREAKER	₹		
							EF-1 E	EXHAUST FAN	76	6W	120 1 60	CONDUCTOR AN CONDUIT SCHEDUCE CC#1		SWITCH TYPE THERMAL SWI			FUSE FU RATING CL			HACR 1	EF-1	
								HRU WALL UNIT RIC WATER HEAT		2.8	208 1 60 120 1 60	CC#4 CC#4	E E	30/2 THERMAL SWI	1	YES	20A RI	K5 30/2 30/	2 1LA	HACR 1 HACR 1,2	TWU-1 WH-1	
							NOTES: 1. LOCATE DISCONN	NECT ADJACENT	TO UNIT.		1 1						1		1			K
							2. PROVIDE 30-AM			SWITCH.												
																Γ	E O U O O O O O O O O O O			<u> </u>		
																		MENT SION 16	SCHE	DULE	KLY	
-																ŀ	Q FURI * COO	NISHED WITH PRDINATE WIT	THE EQUIPMENT THE DIVISION		E	L
																Ł		ITROL INSTAL	LLER ITROL WIRING BY	DIVISION 15		

Harris & Associates.

0 South Suite 350 ry, Utah 84111-1604 -8564 Fax (801) 355-2938

INFORMATION

175 South Main Street, Suite 300 Salt Lake City, Utah 84111 801-328-5151 800-678-7077 FAX 801-328-5155 www.spectrum-engineers.com

SHEET TITLI	E					
I Sch	edules					
REVISIONS		ВУ	DESCRIPTION			
		· · · · · · · · · · · · · · · · · · ·				
\triangle		_				
DRAWN BY	PSS	CHECKED BY	DLA			
PROJECT NO.	06286480	DRAWING NO.	F / O 4			
DATE 2	006-09-07	E-601				